

Foundation coating

Professional Selection T60

The T60 is a professional foundation. This product provides excellent waterproofing of concrete and masonry foundations. Its consistency helps to coat the entire surface including irregularities. Its application is easy at all temperatures.



Advantage

Professional selection

10 years warranty

Prevents deterioration of concrete and masonry

Waterproof the surface by creating a barrier against water and moisture

Easy application at all temperatures

	ınction		

Waterproofing

Building component

Foundation

Surface

Concrete

Masonry

Application tools

Roller

Paint brush

Spray gun

Application temperature

10°C and more preferably. The product will be thicker when the temperature decreases.

3 m2/L

120 ft2/gallon

Service temperature

-40°C to 85°C

Covering rate

Standard

CAN/ONGC 37-GP-6MA

Color

Black

Density

0,90-1,0

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. For the waterproofing of a new foundation, first seal the gap between the footing and the wall foundation using a bead of plastic cement from Thiroco. Use the same product to fill holes, cracks, weak spots in the foundation and the tie rod.



Application

Do not apply if rain is expected. During colder periods, keep the product in a temperate place to facilitate its application. Stir well before application. Apply the product in an thin and even layer. Let dry completely before covering or backfilling to avoid premature product deterioration, thus allowing moisture to infiltrate. Close the container after each use.

Drying

Allow about 24h for the drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

3,78L / 18,9L

Restriction / Caution

Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odors toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

10 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid plant (FOB plant).



2645 B, boul. Terra Jet, Saint Cyrille de Wendover (Qc) J1Z 1B3





DANGER





Flammable liquid and vapour. May be fatal if swallowed and enters airways. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. IF EXPOSED: Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell. IN CASE OF FIRE: Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.